


STRIKER ACHMC

ADVANCED COMBAT HELMET MID CUT | LEVEL IIIA



The Striker ACHMC™ (Advanced Combat Helmet Mid Cut) has been tested to NIJ Standard 0106.01 for Level IIIA threats and MIL-STD-662F for fragmentation. Made from Hybridized Kevlar® and UHMWPE Spectra® fibers, the ACH comes standard with D3O® TRUST Stealth™ 7-pad helmet system, and is available with multiple harness options.

AVAILABLE COLORS



SPECIFICATIONS

- Protection: Level IIIA including frag protection
- NIJ Standard 0106.01 TESTED: This product has been independently tested by an NVLAP accredited NIJ approved laboratory to meet or exceed ballistic resistance as specified under NIJ Standard 0106.01
- MIL-STD-662F: This product has been independently tested by an NVLAP accredited NIJ approved laboratory against frag resistance as specified under MIL-STD-662F
- Materials: Kevlar® fibers and thermoset resin shell construction
- Head Protection: Front, back, crown, and side of the head
- Weight Tolerance: +/- .15 lbs / .068 kg
- Retention: Multiple options available, comes standard with HighCom's 4pt Retention Harness
- Suspension: Multiple options available, comes standard with D3O® TRUST Stealth™ 7-pad system
- Sizing: Circumference is measured around the head, similar to hat sizing. All sizes are measured in inches. If a measurement falls on a dividing line between sizes, select the larger of the two sizes to ensure maximum ballistic protection
- Warranty: 5 years on all ballistic material excluding exterior cover, 1 year on exterior cover material and workmanship

SIZE & WEIGHT CHART

| SIZE | LENGTH | WIDTH | CIRCUMFERENCE | WEIGHT | | |
|------|--------------|--------------|----------------|--------|--------|---------|
| S | 7.1" to 7.6" | 5.6" to 6.0" | 21.1" to 21.9" | 821g | .82 kg | 1.8 lbs |
| M | 7.6" to 7.9" | 6.0" to 6.3" | 21.9" to 22.7" | 894 g | .89 kg | 1.9 lbs |
| L | 7.9" to 8.3" | 6.3" to 6.5" | 22.7" to 24" | 944 g | .94 kg | 2 lbs |
| XL | 8.3" to 8.8" | 6.5" to 7.1" | 24" to 26" | 1007 g | 1 kg | 2.2 lbs |

NIJ 0106.01 HANDGUN THREATS

| PROJECTILE | GR | VEL FT/S | VEL M/S | {+/- FT/S} | {+/- M/S} |
|----------------------------------------------|-----|----------|---------|------------|-----------|
| .357 Magnum Jacketed Soft Point (JSP) | 158 | 1395 | 425 | (+/- 50) | (+/- 15) |
| 9mm Full Metal Jacketed Round Nose (FMJ RN) | 124 | 1400 | 427 | (+/- 30) | (+/- 9) |
| .44 Magnum Semi Jacketed Hollow Point (SJHP) | 240 | 1400 | 427 | (+/- 30) | (+/- 9) |

MIL-STD-662F FRAG THREATS

| PROJECTILE | GR | VEL FT/S | VEL M/S | V50 FT/S | V50 M/S |
|----------------------------|----|----------|---------|----------|---------|
| US MIL-STD Frag 2 gr. RCC | 2 | 4200 | 1280 | 4754 | 1449 |
| US MIL-STD Frag 4 gr. RCC | 4 | 3475 | 1059 | 3595 | 1096 |
| US MIL-STD Frag 16 gr. RCC | 16 | 2475 | 754 | 2457 | 749 |
| US MIL-STD Frag 64 gr. RCC | 64 | 1750 | 533 | 1877 | 572 |
| US MIL-STD Frag 17 gr. FSP | 17 | 2200 | 671 | 2221 | 677 |

ENGINEERED TO PROTECT

HIGHCOMARMOR.COM