

STRIKER HPACHMC

HIGH PERFORMANCE MID CUT | LEVEL IIIA



MIL-STD
662F



0106.01
TESTED



MULTI-HIT
PROTECTION



LIGHTWEIGHT




HIGH
PERFORMANCE

The Striker HPACH™ (High-Performance Advanced Combat Helmet Standard Cut) exceeds MIL-STD-662F frag standards for Level IIIA threats and is tested to NIJ Standard 0106.01. Made from Hybridized Kevlar® and UHMWPE Spectra® fibers, helmet comes standard with D30® TRUST Stealth™ 7-pad helmet system, and is available with multiple harness options.



AVAILABLE COLORS



SPECIFICATIONS

- High-Performance (HP): Frag tested to protect against higher V50 velocities
- Protection: Level IIIA including frag protection
- NIJ Standard 0106.01 TESTED: This product has been independently tested by an NVLAP accredited NIJ approved laboratory to meet or exceed ballistic resistance as specified under NIJ Standard 0106.01
- MIL-STD-662F: This product has been independently tested by an NVLAP accredited NIJ approved laboratory against frag resistance as specified under MIL-STD-662F
- Materials: Hybridized Kevlar® fibers and UHMWPE Spectra® shell construction
- Head Protection: Front, back, crown, and side of the head
- Weight Tolerance: +/- .15 lbs / .068 kg
- Retention: Multiple options available, comes standard with HighCom's 4pt Retention Harness
- Suspension: Multiple options available, comes standard with D30® TRUST Stealth™ 7-pad system
- Sizing: Circumference is measured around the head, similar to hat sizing. All sizes are measured in inches. If a measurement falls on a dividing line between sizes, select the larger of the two sizes to ensure maximum ballistic protection
- Warranty: 5 years on all ballistic material excluding exterior cover, 1 year on exterior cover material and workmanship

SIZE & WEIGHT CHART

SIZE	LENGTH	WIDTH	CIRCUMFERENCE	WEIGHT		
S	7.1" to 7.6"	5.6" to 6.0"	21.1" to 21.9"	918 g	.91 kg	2.02 lbs
M	7.6" to 7.9"	6.0" to 6.3"	21.9" to 22.7"	962 g	.96 kg	2.12 lbs
L	7.9" to 8.3"	6.3" to 6.5"	22.7" to 24"	1110 g	1.11 kg	2.44 lbs
XL	8.3" to 8.8"	6.5" to 7.1"	24" to 26"	1146 g	1.14 kg	2.52 lbs

NIJ 0106.01 HANDGUN THREATS

PROJECTILE	GR	VEL FT/S	VEL M/S	{+/- FT/S}	{+/- M/S}
.357 Magnum Jacketed Soft Point (JSP)	158	1395	425	{+/- 50}	{+/- 15}
9mm Full Metal Jacketed Round Nose (FMJ RN)	124	1400	427	{+/- 30}	{+/- 9}
.44 Magnum Semi Jacketed Hollow Point (SJHP)	240	1400	427	{+/- 30}	{+/- 9}

MIL-STD-662F FRAG THREATS

PROJECTILE	GR	VEL FT/S	VEL M/S	V50 FT/S	V50 M/S
US MIL-STD Frag 2 gr. RCC	2	4200	1280	5059	1542
US MIL-STD Frag 4 gr. RCC	4	3475	1059	4168	1270
US MIL-STD Frag 16 gr. RCC	16	2475	754	3042	927
US MIL-STD Frag 64 gr. RCC	64	1750	533	2188	667
US MIL-STD Frag 17 gr. FSP	17	2200	671	2607	795

ENGINEERED TO PROTECT

HIGHCOMARMOR.COM